



Power Foam®

Carburetor and Induction-System Cleaner for Two- and Four-Stroke Gasoline Engines

AMSOIL Power Foam® (APF) improves engine performance by removing gum, varnish and carbon deposits that affect power, operation, idle and fuel economy. Power Foam cleans intake valves, intake manifolds and throttle plates to keep the combustion intake system running at peak efficiency. Effective in both two- and four-stroke gasoline engines, Power Foam helps reduce engine ping and keeps carburetors and injector systems operating like new. Power Foam is safe for fuel injectors, catalytic converters and emissions-control devices. It will not damage seals, gaskets, rubber or plastic materials commonly used in gasoline engines.



Performance Features

- **Cleans** deposits from ethanol and degraded fuel
- **Removes** gum and varnish
- **Maximizes** horsepower
- **Restores** startability
- **Helps** improve fuel economy
- **Reduces** pollution

Applications

- UTVs/ATVs • Boats • Motorcycles
- Lawn equipment • Tractors • Automobiles

Directions

1. Protect painted surfaces and mass airflow sensors (MAF) from spray.
2. Ensure application is in a well-ventilated area.
3. Run engine to normal operating temperature and remove air cleaner assembly.
4. While engine is running, spray foam directly into throttle body as fast as possible without stalling engine. It is common to have to rev the engine above idle to facilitate this process.
5. Shut off engine and allow to sit for 10-15 minutes.
6. Replace air cleaner.
7. Restart engine. Repeat application of Power Foam as needed.

In extreme cases, disassemble carburetor and soak parts.

Recommendations

Avoid contact with hoses and exterior plastic components. To prevent the dissolving of paint, do not overspray. Clean any overspray immediately to prevent unintentional component damage. Power Foam is not recommended for use in diesel engines, GDI engines or as a general-purpose degreaser.

Disposal

Aerosols may have different disposal requirements than other wastes in your area. Dispose of contents and container in accordance with all federal, state/provincial and local regulations.

TECHNICAL SERVICES

For immediate answers to your technical questions call (715) 399-TECH (8324) between 8 a.m. and 5 p.m. Central time or email tech@amsoil.com.

PRODUCT AVAILABILITY

Power Foam is available in 18-ounce spray cans. Not available in Canada or California.

PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit www.amsoil.com/warranty.aspx.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended applications and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available online at www.amsoil.com or upon request at (715) 392-7101. **Keep Out of Reach of Children.**



Amsoil Dealer John Cardell ZO# 1254295
Cell: (702) 994-4646
Email: john@syntheticmotoroil.me
<https://www.syntheticmotoroil.me>
<https://www.syntheticmotoroil.org>
<https://www.motoroilinfo.com>

AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.

To order Amsoil products by phone please call between the hours of 7AM - 7PM Central Time

Phone: 1-800-777-7094
Referral Number: 1254295

Online Ordering:
<https://amsoilstore.syntheticmotoroil.org>
<https://www.syntheticmotoroil.me/store>